

VERSACOOLER SURFACE-MOUNTED BUBBLERS

Mounted mains-connected bubbler

The VersaCooler Series is a wall-mounted water bubbler offering refrigerated drinking water with both a contactless and vandal-resistant option.



KEY FEATURES

- Vandal resistant manual activation model (AC-PV8ACY-ASM) with mechanically activated push button
- Electronic sensor touch free activation (AC-P8ACTY-ASM) with hands free activation
- Stainless steel top and heavy duty frame
- High efficiency cooling system using R-134a refrigerant
- Built-in 100-micron strainer stops particles before they enter the waterway
- Waterways are lead-free in materials and construction
- Flexible, one-piece water saver bubbler guard
- Basin is designed to eliminate splashing and standing water
- Water-saver bubbler reduces waste water by 50%.
- External stream height adjustment
- Heavy duty galvanised steel frame
- Energy-efficient refrigeration system powers 'ON' only when in use or if water temp increases during period of standby

The heavy-duty galvanised steel frame makes the unit extra durable, perfect for high volume applications. With a basin designed to eliminate splashing and standing water, to reduce waste by 50%.

Also featuring a 100-micron strainer to stop particles entering the leadfree waterway, and with a vandal-resistant & contactless design, the VersaCooler is perfect for schools and other public areas. VersaCooler fountains use R-134a refrigerant and have an efficient, high performing refrigeration system.



Model Information

	AC-P8ACTY-ASM	AC-PV8ACY-ASM
Activation	Contactless (Downward Facing Infrared Sensor)	Mechanical (Vandal Resistant, Touch Button)
Sensor Coverage	Up to 5cm (approx.)	n/a
Filtration	Filter (optional), Built-in 100 micron strainer	
Water Connections	Inlet: 1/2" BSP connector, Drain: 40mm Female Socket (Not trapped)	
Exterior	Antimicrobial ABS Plastic, Brushed Stainless Steel	
Chassis	Heavy Duty Galvanised Steel	
Dimensions	480(H) x 448(W) x 473(D)	
Net Weight	27kg	
Power Supply	220-240V, 50/60 Hz	
Cooling Performance	30 LPH - Rated Capacity & Base Rate - (10°C in 21°C amb. temp.)	
Full Load Amps	2.2 A	
Rated Watts	450 W	
Country of Origin	Mexico	
Certifications	WaterMark, ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS)	
Warranty	1 Year Full, 2 Years Parts Only	

Your Partner in Cool.

**AQUA
COOLER**

TECHNICAL DRAWINGS

VersaCooler (AC-P8ACTY-ASM & AC-PV8ACY-ASM)

